



Using Real-time Smoothness Measurements to Improve Concrete Pavement Quality and Save Money

Workshop Agenda (4-Hour Workshop Format)

WORKSHOP OBJECTIVES

- x To educate pavement practitioners on the fundamentals of concrete pavement smoothness measurement and interpretation.
- To reinforce best practices for concrete paving operations to achieve ride quality requirements.
- To demonstrate Real-Time Smoothness technology as a tool for improving concrete pavement smoothness.

WORKSHOP SCHEDULE

- 0:15 Session 1: Welcome and Overview
- 0:30 Session 2: Fundamentals & Importance of Pavement Smoothness
- 0:45 Session 3: RTS Measurement Technology and Practices
- 0:30 Session 4: Fundamentals of Ride Quality and Current Practices for IRI Specs
- 0:45 Session 5: Best Practices for Concrete Paving Operations
- 1:00 Session 6: Using RTS Technology to Improve PCCP Smoothness
- 0:15 Q&A

WORKSHOP INSTRUCTORS

Gary Fick, Trinity Construction Management Services, Inc
gfick@trinity-cms.com
(405) 823-2313

David Merritt, The Transtec Group, Inc.
dmerritt@thetranstecgroup.com
(512) 451-6233

FHWA/SHRP2 CONTACT

Stephen Cooper, FHWA
Stephen.J.Cooper@dot.gov
(410) 962-0629

FOR MORE INFORMATION

[http://www.fhwa.dot.gov/goshrp2/Solutions/Renewal/RO6E/Tools to Improve PCC Pavement Smoothness During Construction](http://www.fhwa.dot.gov/goshrp2/Solutions/Renewal/RO6E/Tools_to_Improve_PCC_Pavement_Smoothness_During_Construction)



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

Using Real-time Smoothness Measurements to Improve Concrete Pavement Quality and Save Money

Session 1: Welcome and Overview

U.S. Department of Transportation
Federal Highway Administration

AASHTO
THE VOICE OF TRANSPORTATION

TRANSPORTATION RESEARCH BOARD
OF THE NATIONAL ACADEMIES




Session 1: Welcome and Overview

- Introductions
- Workshop Overview and Objectives
- Introduction to Real-time Smoothness (RTS) Technology

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

2



Introductions

- Name
- Agency and location
- Interest in concrete paving and smoothness measurements
- Experience with RTS technology

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

3



Instructors

Gary Fick
Trinity Construction Management Services, Inc.
(Edmond, OK)

David Merritt
The Transtec Group, Inc.
(Austin, TX)

National Concrete Pavement
Technology Center



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

4



Who Sponsors this Effort?

- SHRP2 Solutions is a collaborative effort of AASHTO, FHWA and TRB
- Funding research projects for:
 - Making highways safer
 - Fixing deteriorating infrastructure
 - Reducing congestion


U.S. Department of Transportation
Federal Highway Administration

AASHTO
THE VOICE OF TRANSPORTATION

TRB
TRANSPORTATION RESEARCH BOARD
OF THE NATIONAL ACADEMIES

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

5



SHRP2-R06(E)

- 2009 - 2011 SHRP2 effort to demonstrate and evaluate existing RTS measuring technologies.
 - Georgia, Arkansas, Texas, Michigan & New York
- Developed draft model specifications and guidelines.
- Final report online:
<http://www.trb.org/Main/Blurbs/167282.aspx>



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

6

Implementation Support

Current effort involves:

- Equipment Loan Program
- Showcases
- **Workshops**
- Documentation of results/case studies
- Specification Refinement

National Concrete Pavement Technology Center 

 7

Workshop Goals

- To educate pavement practitioners on the fundamentals of concrete pavement smoothness measurement and interpretation.
- To reinforce best practices for concrete paving operations to achieve ride quality requirements.
- To demonstrate Real-Time Smoothness technology as a tool for improving concrete pavement smoothness.

 8

Workshop Topics

- Measuring Pavement Profiles
- Introduction to Real-Time Smoothness Technology
- Interpreting and Analyzing Pavement Profiles
 - What is the IRI and what are current specification requirements?
 - What is localized roughness?
 - ProVAL software analysis tools
- Best Practices for Concrete Paving Operations
- Using RTS Technology to Improve Smoothness

 9

Workshop Outline

- Session 2: Fundamentals & Importance of Pavement Smoothness
- Session 3: RTS Measurement Technology and Practices
- Session 4: Fundamentals of Ride Quality and Current Practices for IRI Specs
- Session 5: Best Practices for Concrete Paving Operations
- Session 6: Using RTS Technology to Improve PCCP Smoothness

 10

What is RTS Measurement?


Real-time smoothness refers to measuring and evaluating the concrete pavement surface profile during construction, somewhere along the paving train while the concrete surface is still wet (plastic).



 11

With RTS Measurements You Can...

- Identify events during concrete paving that affect smoothness.
- Examples:
 - Dowel basket rebound
 - Concrete load effects
 - Stringline sag
 - Localized roughness
 - Etc.



 12

Questions?

Next:

- **Session 2: Fundamentals & Importance of Pavement Smoothness**

 FOR THE ROAD AHEAD

13



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD


Using Real-time Smoothness Measurements to Improve Concrete Pavement Quality and Save Money

Session 2: Fundamentals and Importance of Pavement Smoothness

U.S. Department of Transportation
Federal Highway Administration

AASHTO

TRANSPORTATION RESEARCH BOARD
OF THE NATIONAL ACADEMIES




Session 2: Fundamentals and Importance of Pavement Smoothness

- Importance of Pavement Smoothness
- Fundamentals of Pavement Smoothness Measurement
 - What is a pavement profile?
 - How do we measure pavement profiles?

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

2




Importance of Pavement Smoothness

Key reasons why smoothness is important (Agency Perspective):

1. It's important to the user (taxpayer).
2. Smoother roads last longer.
3. Smoother roads stay smoother longer.
4. Smoother roads are safer.
5. Smoother roads save money.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

3




Importance of Pavement Smoothness

Key reasons why smoothness is important (Contractor Perspective):

1. Reflects the quality of your work.
2. \$\$\$


SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

4



How do we measure smoothness?


A **profile** is a slice of the road surface following an imaginary line



Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

5



How do we measure smoothness?

A **profile** is a slice of the road surface following an imaginary line




Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

6

How do we measure smoothness?

A **profile** is a slice of the road surface following an imaginary line



Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

7

Measuring Profiles: Rolling Straightedge




Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

8

Measuring Profiles: Rolling Straightedge

Rolling Straightedge Response




Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

9

Measuring Profiles: Rolling Straightedge

Rolling Straightedge Response




Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

10

Measuring Profiles: Rolling Straightedge

Frequency Response



Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

11






Measuring Profiles: Profilograph







Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

12





Other Profiler Types

SSI Walking Profiler



SurPro Walking Profiler



Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

25

Other Profiler Types

Real-Time Profiler (Inclinometer based)




Ultrasonic Sensors



Laser Sensors

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

26



Recap

- We want to measure the “actual profile” or actual shape of the pavement surface with our profiling device.
- High Speed/Lightweight Inertial Profilers or Walking Profilers give us the best representation of the actual profile.
- RTS profilers give us this same information while the concrete is still plastic.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

28

Questions?

Next:

- **Session 3 - RTS Measurement Technology and Practices**

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

29



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD


Using Real-time Smoothness Measurements to Improve Concrete Pavement Quality and Save Money

Session 3: RTS Measurement Technology and Practices

U.S. Department of Transportation
Federal Highway Administration

American Association of State Highway and Transportation Officials
AASHTO

TRANSPORTATION RESEARCH BOARD
OF THE NATIONAL ACADEMIES




Session 3: RTS Measurement Technology and Practices

- Benefits and limitations of RTS technology
- Overview of current RTS devices – Ames RTP & GOMACO GSI
- Options for mounting RTS devices (paver/work bridge/cure cart, wheelpath/center of lane, etc.)
- Examples of RTS output/profile trace
- Best practices/lessons learned

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

2




What is RTS Measurement?

Recap: **Real-time Smoothness** refers to measuring and evaluating the concrete pavement surface profile during construction, somewhere along the paving train while the concrete surface is still wet (plastic).



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

3




RTS Measurements: Benefits

- Innovative **tools** for evaluating concrete pavement smoothness in real time.
- Tools that can be used for **quality control** and **process improvements**.
- **Process improvements** as a result of timely feedback.
- Improved understanding about how **construction artifacts** can affect smoothness.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

4




RTS Measurements: Limitations

- Not a replacement for **conventional profiling** for acceptance.
- Not a replacement for **better practices** to construct smoother pavements.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

5



RTS Profilers

Paver-Mounted GOMACO Smoothness Indicator (GSI)



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

6

RTS Profilers

Stand-Alone GOMACO GSI Machine



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

7

RTS Profilers

Ames Engineering Real Time Profiler (RTP)



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

8

RTS Mounting

Possible sensor configurations:

- Mounted to the back of the paver (main pan or finish pan).
- Mounted to a trailing work bridge or texture/cure cart.
- Dedicated machine (GSI) located behind the finishers or texture/cure cart.
- Combination of sensors, such as a paver mounted followed by sensors on a work bridge/stand-alone machine.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

9

RTS Mounting

Lateral configurations:

- Mounted in the lane wheelpaths (corresponding to hardened profile acceptance).
- Mounted mid-lane.
- Mounted where profile is traditionally rougher (paver configuration dependent).

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

10

RTS Mounting

- GSI and Ames RTP mounted to the back of a paver in the wheelpaths:



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

11

RTS Mounting

- GSI machine, after finishers, before texture/cure cart:



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

12

RTS Mounting

- Ames RTP equipment mounted to a self-propelled work bridge:



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

13

RTS Mounting

- GOMACO GSI and Ames RTP mounted to a towed work bridge:



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

14

RTS Measurements

- Real-time feedback, viewing and analysis capabilities:



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

15

RTS Measurements

- Real-time feedback, viewing and analysis capabilities:

GSI



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

16

RTS Measurements

- Real-time feedback, viewing and analysis capabilities:

Ames RTP



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

17

Contractor Feedback/ Lessons Learned

- Contractor and agency can “see” things in real-time that used to take 24-48 hours
- RTS overall improves the paving process through better quality and improved efficiency
- Well suited for:
 - Identifying operational changes on smoothness
 - Tuning the paver
 - Quality control
 - Troubleshooting and correcting problems early

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

18

Contractor Feedback/ Lessons Learned

- Contractors using RTS equipment are observing ~20-50% difference between real-time (wet) and QC numbers (hardened)
- 100 in/mi real-time is typically equivalent to 75 in/mi hardened
 - The higher the real-time numbers the greater the percent difference.
 - The lower the real-time numbers the tighter the correlation with QC numbers.



19

Contractor Feedback/ Lessons Learned


- Why is the real-time profile rougher than the hardened?
 - Fixed height of real-time sensor (no accelerometer)
 - Vibrations from the paver (measurement error) are interpreted as profile deviation
 - Hand finishing removes localized roughness, especially true for higher real-time readings



20

Contractor Feedback/ Lessons Learned

- Good, but not perfect, between RTS and hardened profiles




21

Contractor Feedback/ Lessons Learned

- Does it matter that real-time data is rougher than hardened profile data?
 - Concentrate on lowering the real-time numbers
 - This will translate to lower hardened numbers (smoother pavement)



22

Contractor Feedback/ Lessons Learned

- Equipment adjustments that can be reflected in RTS measurements:
 - Paver speed
 - Vibrator frequency
 - Vibrator height
 - Sensitivity of paver elevation controls (hydraulics and stringless)
 - Oscillating correcting beam frequency
 - Draft (angle of attack)
 - Others



23

Contractor Feedback/ Lessons Learned

- Process adjustments that can be reflected in RTS measurements:
 - Concrete workability
 - Concrete delivery/spreading procedures
 - Stringline tension
 - Hand finishing techniques (when sensors are mounted to a trailing work bridge)
 - Concrete uniformity
 - Stopping the paver vs. slowing the paver
 - Concrete head (height and uniformity)
 - Others



24

Contractor Feedback/ Lessons Learned

- **It takes changing the current mindset:**
 - Finishing crews used to actively finishing to meet smoothness specifications
- **Now RTS equipment allows crews to:**
 - Monitor smoothness
 - Locate and verify bumps/deficiencies,
 - Check with a straightedge
 - Try to correct it



25

Contractor Feedback/ Lessons Learned

- **Paving Crew Training**
 - Current mindset: extra person needed to monitor RTS device
 - Not necessarily correct - lead finisher tends to understand the device and assumes the role to monitor it
- **Download the RTS files at the end of each day for analysis.**
 - ProVAL comparisons of real-time (wet) vs. QC (hardened) measurements



26

Contractor Feedback/ Lessons Learned

- **Tool for paving foreman, paver operator.**
 - Monitor for equipment mechanical problems
 - Effect of events on smoothness: paver stops, paver adjustments, etc.
- **Tool for finishing crews to monitor smoothness.**
 - Typically monitor 100-ft average IRI
- **Preferred mounting location is to the back of the paver.**



27

Questions?

Next:

Session 4 – Fundamentals of Ride Quality and Current Practices for IRI Specs.



28

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

Using Real-time Smoothness Measurements to Improve Concrete Pavement Quality and Save Money

Session 4: Fundamentals of Ride Quality and Current Practices for IRI Specs

U.S. Department of Transportation
Federal Highway Administration

American Association of State Highway and Transportation Officials
AASHTO

TRANSPORTATION RESEARCH BOARD
OF THE NATIONAL ACADEMIES

Session 4: Fundamentals of Ride Quality and Current Practices for IRI Specs

- Where did IRI come from?
- Common IRI surrogates found in specifications: MRI and HRI
- ProVAL software for analyzing profile data.
- Current practices for concrete pavement smoothness specifications nationally.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

2

Response-Type Systems

Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

3

Response-Type Systems

Display: 12.3

Roadmeter/Roughometer

Suspension Motion

Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

4

Response-Type Systems

Response-Type Trailer

Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

5

International Roughness Index (IRI)

What is IRI?

Measured Profile →

Body Mass

Suspension Spring and Damper

Axle Mass

Tire Spring

Quarter-Car Model → IRI

Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

6

International Roughness Index (IRI)




Quarter-Car Simulation



Source: FHWA ProVAL Workshop



7



- ### IRI Reporting Options
- **Overall Roughness**
 - Single value for the IRI of the profile trace
 - **Fixed Interval Report**
 - IRI reported on a lot-by-lot basis
 - **Continuous Roughness Report**
 - IRI reported based on a moving average "baselength"
- 
- 11

- ### Half-Car Roughness Index (HRI)
- Calculated from two profiles
 - The profiles are averaged point-by-point to create an "average" profile
 - The IRI algorithm is applied to the resulting profile
- 
- 12

Half-Car Roughness Index (HRI)

Source: FHWA ProVAL Workshop

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

13

Mean Roughness Index (MRI)

- Calculated from two profiles (generally from the two wheelpaths).
- The IRI algorithm is applied to each profile separately.
- Computed IRI values are averaged and reported as MRI.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

14

Localized Roughness

- Isolated areas that contribute disproportionately to overall roughness.
- “Hot Spots” or “Must Grinds”
- Identified using:
 - Short baselength continuous roughness (IRI) reports
 - Short segment fixed interval IRI
 - Profile moving average
 - Profilograph Simulation
 - Straightedge

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

15

Evaluation of Profiles: ProVAL Software

www.RoadProfile.com

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

16

What is ProVAL?

- Software application to view and analyze pavement profiles in many different ways.
- Easy to use and yet powerful to perform many kinds of profile analyses.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

17

Key ProVAL Modules

- **Roughness Report**
 - Compute and summarize IRI for profiles.
 - Identify Areas of Localized Roughness.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

18

Key ProVAL Modules


- **Profile Synchronization**
 - Line up repeat profile runs.
- **Smoothness Assurance Module (SAM)**
 - Diamond grinding simulation
 - Side-by-side comparison of profile and roughness



19


Key ProVAL Modules

- **Power Spectral Density (PSD)**
 - Identify dominating (repeating) features to contribute roughness.
 - Helps to identify potential issues in the paving operation.



20

Power Spectral Density (PSD)




15' Spacing



21

PCC Pavement Smoothness Specifications




Merritt et al. 2015



22

PCC Pavement Smoothness Specifications




Merritt et al. 2015



23

PCC Pavement Smoothness Specifications



Merritt et al. 2015



24

PCC Pavement Smoothness Specifications

- Summary of IRI-based specification thresholds for PCC pavements:

		Incentive Upper Limit	Full Pay Lower Limit	Full Pay Upper Limit	Disincentive Lower Limit	Disincentive Upper Limit	Threshold for Correction
MRI & IRI (22 states)	min	39.9	40.0	54.0	54.1	67.5	60.0
	max	70.0	71.0	93.0	93.1	140.0	150.0
	avg.	56.2	56.5	71.7	72.5	95.3	96.9
IRI (CO only)		57.9	58.0	67.0	67.1	85.0	85.0

Merritt et al. 2015

PCC Pavement Smoothness Specifications

- Comparison of specification thresholds for asphalt and concrete pavement for IRI/MRI:

Merritt et al. 2015

PCC Pavement Smoothness Specifications

- Range of Incentive/Disincentives applied for ride quality:

Pay Adjustment Basis		Maximum Incentive	Maximum Disincentive
\$ per lot (0.1 mi) 9 states	min	\$200	-\$250
	max	\$1,600	-\$1,750
	avg.	\$879	-\$900
\$ per lot (\$V) 2 states	min	\$1.40	-\$1.12
	max	\$1.40	-\$1.40
	avg.	\$1.40	-\$1.26
\$ per lot (1.0 mi) 1 state		\$7,350	-\$7,350
\$ per lot (0.01 mi) 1 state		\$50	-\$500
\$ per lot (500 ft.) 1 state		\$250	-\$250
Extended Pay Adjustment \$ per lot (0.1 mi) 13 states (NJ excluded)	min	\$200	-\$250
	max	\$1,600	-\$1,750
	avg.	\$825	-\$831
Percent Contract Price 7 states	min	102%	90%
	max	108%	50%
	avg.	105%	75%

Merritt et al. 2015

PCC Pavement Smoothness Specifications

- Summary of localized roughness provisions for IRI-based specifications:

Method	Number of States		Range	
	Asphalt	Concrete		
Continuous IRI (25 ft. baselength)	11	12	80 in/mi	200 in/mi
Fixed Interval IRI	4	4	25 ft. segment: 150-160 in/mi	0.01 mi (52.8 ft.) segment: 100-125 in/mi
Profile Moving Average (25 ft. baselength)	4	1	0.15 inches	0.4 inches
Profilograph Simulation (25 ft. baselength)	2	2	0.3 inches	0.4 inches
Straightedge Only	18	4	1/8-inch in 16 ft.	1/4-inch in 10 ft.

Merritt et al. 2015

PCC Pavement Smoothness Specifications

- Range of Disincentives applied for localized roughness:

	Concrete Pavement (3 states)
Min	-\$10
Max	-\$250
Average	-\$173

Merritt et al. 2015

Recap

- ✓ We discussed what the IRI is and where it came from.
- ✓ We discussed ProVAL as a tool for analyzing profile data (from RTS or hardened profiles).
- ✓ We discussed current practices for IRI specifications for concrete paving.

Merritt et al. 2015

Questions?

Next:
Session 5 – Best Practices for Concrete Paving Operations



31

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

Using Real-time Smoothness Measurements to Improve Concrete Pavement Quality and Save Money

Session 5: Best Practices for Concrete Paving Operations

U.S. Department of Transportation
Federal Highway Administration

AASHTO

TRANSPORTATION RESEARCH BOARD
OF THE NATIONAL ACADEMIES

Session 5: Best Practices for Concrete Paving Operations

- Key aspects of concrete paving that affect smoothness.
- Importance and potential cost-savings of identifying smoothness issues during construction (real-time).

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

2

In the Beginning ...

- A brief history of surface transportation:
Walking, horse, camel or llama before 1790

Timeline: 1700 (Walking) → 1800 (Horse) → 1900 (Camel/Llama) → 2000 (Airplane)

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

3

1924

Crested Co. Kansas
Pittsburg, Mo. Mo.
1924

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

4

Circa 1950

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

5

1968

McPherson County, Kansas

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD




6



Ten Commandments of Concrete Pavement Smoothness (1988)

1. Develop a smoothness plan for the project.
2. Develop an accurate field survey for stringline/ stringless controls.
3. Properly prepare the grade, providing a stable form or track line.
4. Set up proper forms properly for fixed-formed paving.
5. Use a consistent concrete mixture appropriate for the paving method.
6. Deliver and place concrete consistently.
7. Set-up and operate the paver steadily.
8. Fasten dowels/ reinforcing securely and use "bump-free" construction joints (headers).
9. Use only necessary and appropriate finishing techniques.
10. Apply texturing and curing with care.

Source: Chapin CIPHER, CMI Corp.



Mixture Factors

- Combined gradation
- Between batch uniformity
- Uniform delivery of concrete

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

12

Combined Gradation

Remember the purpose of an optimized gradation:


- Economically combining aggregate particles to achieve the desired objectives of:
 - Reduced paste content
 - Improved workability
 - Durability
- An optimized mixture must be workable in the field to achieve durability
- The **Tarantula Curve** was developed concurrently with a lab test that evaluates a concrete mixture's response to vibration



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

13

Combined Gradation: The Tarantula curve



Excessive amount creates workability issues.

Excessive amount that decreases workability and promotes segregation and edge slumping.

Creates surface finishability problems normally associated with manufactured sands.


Not in Scope of work

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

14

Combined Gradation: Tarantula Curve Validation

Minnesota DOT implements a combined gradation specification in the late 1990s (data from Maria Masten, MnDOT).




1996-1998

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

15

Combined Gradation: Tarantula Curve Validation

With added experience, the field mixtures continue to be refined and further reflect the Tarantula Curve recommendations .



Minnesota 2010
98% of mixtures met the sand criteria

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

16

Combined Gradation: Best Practices

- The distribution of fine sand can vary largely without affecting the workability.
- An aggregate volume between 24% to 34% is recommended for #30 - #200.
 - This range was similar for multiple gradations and aggregate sources.
- More than 20% retained on the #30 sieve size created finishing issues.




SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

17

Combined Gradation Tarantula Curve Example

FHWA mobile lab – project A



Fine Sand

Coarse Sand

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

Images from Jagan Gudimetta 18

Combined Gradation Tarantula Curve Example

FHWA mobile lab – project A




SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

Images from Jagan Gudimetta 19

Combined Gradation Tarantula Curve Example

FHWA mobile lab – project B



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

Images from Jagan Gudimetta 20

Combined Gradation Tarantula Curve Example

FHWA mobile lab – project B



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

Images from Jagan Gudimetta 21

Between Batch Uniformity

Consistent combined gradation and water content

- Scales in tolerance
- Uniform stockpile moistures
- Eliminate stockpile segregation



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

22

Uniform Delivery of Concrete

Translates to minimizing paver stops

- Plant production capacity must be able to feed the paver



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

23

Paving Factors

- Track line
- Stringline/Stringless model
- Paver setup
 - Draft/Lead
 - Sensitivities
 - Vibrator frequency
 - Vibrator height
 - Float pan
- Concrete head
- Curing and texturing



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

24

Track Line

Minimize extreme leg barrel movements:

- Profile – trimmed or stabilized base placed with grade control
- Stability – non-yielding and non-pumping
- Width – full width of track supported



25

Track Line




26

Stringline

- Adjusted for smoothness
- Property and uniformly tensioned
- Pin spacing




27

Stringless Model


- Smooth transitions
- Point spacing or true curves
- Control points




28

Paver Setup

- Draft/Lead – paver should be as flat as you can get it




29

Paver Setup

- Sensitivities
 - Sensors
 - Stringless





30

Paver Setup

- **Vibrator frequency**
 - Adjust for paving speed
 - Adjust for mixture
 - Slower at edges



The image shows a control panel on the left with a digital display and several buttons. On the right, a perspective view of a concrete paver is shown from underneath, highlighting the vibrator mechanism.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

31

Paver Setup

- **Vibrator height – adjust for base stiffness and optimize for smoothness**



The image shows a close-up of the vibrator rollers on a concrete paver, illustrating the adjustment point for vibrator height.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

32

Concrete Head

- Starts with subbase uniformity (grade control)
- Maintain a uniform head pressure



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

33

Concrete Head



The image shows a close-up of the concrete head of a paver. Red arrows point to specific components: plow, metering gate/strikeoff, head in grout, and box.


plow
metering gate/strikeoff
head in grout
box

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

34

Curing and Texturing

- Cure before any surface evaporation occurs to reduce warping.
- **Texture**
 - Minimize positive texture
 - Uniform texture depth



The image contains two photographs. The left one shows a close-up of a textured concrete surface with a yellow measuring tape. The right one shows a long, straight concrete slab being cured with a white material.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

35

Hand Finishing?

- Is it necessary?



The image shows a wide view of a concrete slab being finished. A worker is using a hand tool on the surface, with other equipment and vehicles visible in the background.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

36

Hand Finishing?

- Does it improve the pavement smoothness?



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

37

Human Factors

- Training
- Experience
- Communication
- Empowerment



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

38

Human Factors

- Training
 - Everyone on the project contributes to smoothness
 - Each crew member should understand how their tasks impact smoothness – the “BIG PICTURE”



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

39

Human Factors

- Experience
 - “The only source of knowledge is experience.” (Einstein)
 - Crew retention and continuity is essential



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

40

Human Factors

- Communication
 - “The single biggest problem in communication is the illusion that it has taken place.” (George Bernard Shaw)
 - Establish clear lines of communication, so that everyone is on the same page
 - Radios, phones, hand signals, etc.
 - Listen to crew members



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

41

Human Factors

- Empowerment
 - Encourage innovation
 - Enable decision making



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

42

Summary of Best Practices

Putting it All Together

A Venn diagram with three overlapping circles: a red circle on the left labeled 'Mixture Factors', a purple circle on the right labeled 'Paving Factors', and a green circle at the bottom labeled 'Human Factors'. The central area where all three circles overlap is shaded grey and has an arrow pointing to it from the text 'The "Sweet Spot"'. To the left of the circles is a small graphic of colorful interlocking puzzle pieces.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

43

Questions?

Next:
Sessions 6: Using RTS Technology to Improve Concrete Pavement Smoothness

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

44



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD


Using Real-time Smoothness Measurements to Improve Concrete Pavement Quality and Save Money

Session 6: Using RTS Technology to Improve Concrete Pavement Smoothness

U.S. Department of Transportation
Federal Highway Administration

American Association of State Highway and Transportation Officials
AASHTO

TRANSPORTATION RESEARCH BOARD
OF THE NATIONAL ACADEMIES




Session 6: Using RTS Technology to Improve Concrete Pavement Smoothness

- Introduction to using RTS Equipment.
- Experiences from RTS equipment loan program to date.

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

2




Reasons for Using RTS Equipment

- Reduce disincentives
- Increase Incentives
- Anticipated change in smoothness acceptance requirements
 - PrI to IRI
 - Change in localized roughness specification limits

QUALITY ✓

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

3




RTS Systems – Which One is Best?

- They both do the same thing - the correct question is, "which one is best for me?"
- Factors to consider:
 - Ease of mounting and switching between multiple pavers
 - Field ruggedness
 - Familiarity with Ames lightweight profiler systems
 - Laser vs. ultrasonic sensors



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD



RTS Mounting Locations

- Typically center of each driving lane
- Adjust this for special situations, when tuning the paver:
 - Tie bar insertion issues
 - One side of the paver is consistently rougher

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

5



RTS Mounting Locations



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

6


RTS Systems: Daily Setup and Shutdown

- **Start-up - approximately 5 minutes**
 - Install sensors and DMI
 - Connect cables
 - Input starting station and direction
 - Start the system
- **Shut-down – approximately 5 minutes**
 - Stop the system
 - Download data to a USB drive
 - Disconnect cables
 - Remove sensors and DMI




7

RTS Systems: GOMACO GSI Setup



8

RTS Systems: Ames RTP Setup



9

Using RTS Systems

- **Step 1 – Establish a baseline**
 - Monitor results for 1 to 2 days.
 - Keep processes static, but make ordinary adjustments.
 - Observe typical responses to the ordinary adjustments and make notes or add event markers in the RTS.
 - Mixture
 - Vibrators
 - Speed
 - Head
 - Paver stops
 - Etc.




10

Using RTS Systems

- **The RTS results are higher than the QC hardened profiles – what's up with that?**
 - Don't panic
 - Just focus on making the RTS results better (lower IRI)
 - QC profiles will improve as well




11

Using RTS Systems

- **Step 2 – Pick the low hanging fruit**
- **Eliminate large events that cause excessive localized roughness.**
 - Stringline/stringless interference
 - Paver stops
 - Padline issues
 - Etc.




12

Localized Roughness Events

- Stringless system interference



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

13

Localized Roughness Events

- Running the paver out of concrete



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

14

Localized Roughness Events

- Stopping the paver

St Start	St End	Description	Date/Time
91+10 st	0+00 st	PAVER STOP	10:58a 10/01
91+71 st	0+00 st	PAVER STOP	11:13a 10/01
92+02 st	0+00 st	PAVER STOP	11:28a 10/01
94+09 st	0+00 st	PAVER STOP	12:13a 10/01
97+14 st	0+00 st	PAVER STOP	01:02p 10/01
97+41 st	0+00 st	PAVER STOP	01:08p 10/01

SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

15

Using RTS Systems

- Step 3 - Adjust the paving process to improve overall smoothness
 - Maintain a consistent head
 - Lead/draft to get the paver as flat as possible
 - Sensitivities
 - Vibrators (height and frequency)
 - Mixture
 - Paver operation
 - Paving speed



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

16

Overall Smoothness

- Eliminating big events gives you a new "baseline" to adjust from.
 - Systematically make changes in small increments.
 - Get a minimum of 0.1 mile with consistent paving (no big events) and then evaluate if the adjustment made things smoother.
 - Continue adjusting in small increments and evaluating every 0.1 mile.




SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

17

Overall Smoothness

- Stay focused and incredible things can happen
 - Over a mile paved per day - average IRI = 28 in/mi:



SHRP2 SOLUTIONS
TOOLS FOR THE ROAD AHEAD

18

Using RTS Systems


- **Step 4 – Identify repeating features using a ProVAL PSD plot and adjust processes when possible.**
 - Joints
 - Dumping/Spreading loads
 - CRCP bar supports



19

Repeating Features


- What repeating feature shows up here?
- What can you do to mitigate this feature?




20

Repeating Features


- What is occurring here at 10.5'?




21

Repeating Features

- CRCP – what is contributing to roughness here?




22

SHRP2-FHWA RTS Equipment Loan

- **Equipment Loans to Date**
 - Idaho, I-84
 - Nebraska, I-80
 - Michigan, I-69
 - Texas, SH99
 - Pennsylvania, I-81
 - Iowa, Lyon Co. L-26
 - Illinois, I-90
 - Utah, I-215
 - Utah, I-15
 - California, SR-46



23

Idaho, I-84

- **Ames RTP**
- **Project Info**
 - Widening of an existing interstate pavement
 - 12" JPCP over asphalt base (portion over agg. base)
 - 24' paving width, 15' joint spacing with dowel baskets
 - Stringless paving
 - Concrete deposited in front of paver with placer.








24






Idaho, I-84






- **Monitoring (4 days of paving)**
 - Paver stops/starts
 - Concrete load consistency (wet/dry loads)
 - Concrete head in front of paver
 - Concrete level in grout box
 - Use of auto-float
- **Hardened profile data collected the day following paving.**







25









Iowa, Lyon County L-26

- Ames RTP
- Project Info
 - Mainline overlay paving of county road
 - 5" JPCP over existing HMA
 - 24' paving width, 6' x 6' joint spacing
 - No steel – except in transition sections
 - Stringless paving
 - Concrete deposited in front of paver

47



Iowa, Lyon County L-26

- PSD
 - No short wavelength content – no steel, minimal curling/warping due to small slab dimensions
 - 55' wavelength – 3D model?

SHRP2 SOLUTIONS
FOCUS FOR THE ROAD AHEAD

49

Iowa, Lyon County L-26

- Sensitivity adjustment on the right side of the paver
- What about hardened?

SHRP2 SOLUTIONS
FOCUS FOR THE ROAD AHEAD

50

Iowa, Lyon County L-26

- Comparison of real-time and hardened

HARDENED PROFILE SEGMENTS	LENGTH (ft)	MATCHED 6.10 m SEGMENT #	RIGHT SIDE OF PAVEMENT		LEFT SIDE OF PAVEMENT		Δ RTP-HRD (m/m)		
			HRD IRI LT (SB) (m/m)	RTP IRI LT (SB) (m/m)	HRD IRI RT (NB) (m/m)	RTP IRI RT (NB) (m/m)	SB	NB	
-105+52.00									
-101+24.00	528		88		79				
-99+66.00	528		64		69				
-90+68.00	528	1	50	49	48	55	-1	7	
-85+40.00	528	2	69	76	55	60	7	25	
-80+12.00	528	3	56	60	46	61	4	15	
-74+84.00	528	4	52	54	53	62	2	9	
-73+63.00	139		78		61	65	0	24	
-68+17.00	528		63		67				
-62+89.00	528	5	48	64	48	63	16	15	
-57+61.00	528		51		52				
-52+33.00	528	6	57	64	54	71	-3	17	
-50+91.00	142		43	58	48	54	15	6	
-45+63.00	528	7	53	46	52	62	-7	10	
-40+35.00	528	8	39	58	58	67	-1	9	
-35+07.00	528	9	51	50	58	60	-1	2	
-29+79.00	528		54		51				
-24+51.00	528	10	49	45	57	64	-4	7	
-19+23.00	528	11	66	66	65	64	6	-1	
-12+38.00	188		52	55	47	45	3	-2	
AVERAGE			57.7	58.1	56.2	64.5	2.6	10.9	

SHRP2 SOLUTIONS
FOCUS FOR THE ROAD AHEAD

51

Utah I-15

- IRI on 150 ft base-length from ProVAL
- Matches what we were seeing in real-time the previous night
- IRI cycles up and down every ± 350'? Most pronounced on the right side of the paver, but still present on the left.

SHRP2 SOLUTIONS
FOCUS FOR THE ROAD AHEAD

52

Utah I-15

- IRI cycles up and down every ± 350'?
- Also shows up in the hardened profile.

SHRP2 SOLUTIONS
FOCUS FOR THE ROAD AHEAD

53

Illinois I-90

- DBI malfunction during paving.
- Do finishers help?

SHRP2 SOLUTIONS
FOCUS FOR THE ROAD AHEAD

54